



## Model: 4.3L TKS

Power	190HP (142 KW)
Full Throttle Range	4400 - 4800
Displacement	262 CID (4.3L)
Engine Type	V6
Bore & Stroke	4.00" X 3.48" (101mm X 88mm)
Compression Ratio	9.4 : 1
Fuel Requirement	87 Octane (R+M)/2
Fuel System	2V Carb with Turn Key Start & Electrical Fuel Pump
Induction System	dual plane iron intake manifold
Ignition System	thunderbolt v
Charging System	65 Amp / 917 Watt Alternator
Water Drain System	Multi point drain - hand removable blue drain plugs
Exhaust System	EDP Coated Iron Manifold with EDP Coated Dry-joint Elbow
Cooling System	Thermostatically Controlled, Raw Water
Accessory Drive System	Serpentine Belt
Recommended Engine Oil	MerCruiser Full Synthetic Engine oil - SAE 20 W 40
Engine Alarm System	Low Oil Pressure, High Water Temperature, low drive lube
Alpha Ratios	1.62, 1.81(P), 2.0
Dimensions (L x W x H) in	28 x 30 x 21
Dimensions (L x W x H) mm	696 x 740 x 533
Weight w/ Alpha (lbs/kg)	848/385
Optional Fresh water cooling	Available
Warranty	1 year or 500 hours, whichever is earlier