



## Model: 75 HP

|   |  |
|---|--|
| HP / kW                                       | 75 / 56  |
| Full Throttle RPM                             | 5000 - 6000                                      |
| Bore x Stroke (in / mm)                       | 3.23 x 3.23 in<br>82 x 82 mm                     |
| Cylinder/Configuration                        | I-4  |
| Displacement (CID/cc)                         | 105.7 / 1732                                     |
| Fuel Induction System                         | 4-valves per cylinder, dual overhead cam (DOHC)  |
| Alternator Amp                                | 50 amp / 630 watt                                |
| Starting                                      | Electric (Turn Key)                              |
| Gear Case Ratio                               | 2.33 : 1   |
| Steering                                      | Big Tiller Compatible<br>Mercury Remote Steering |
| Recommended Oil                               | Mercury 4-Stroke Outboard Oil                    |
| Recommended Fuel                              | 87 Octane up to 10% ethanol                      |
| Engine Protection Operator Warning System     | Smartcraft Engine Guardian                       |
| Compatible with Smartcraft Digital Technology | Yes  |
| Trim System                                   | Power Trim and Tilt                              |
| Shaft Length                                  | L - 20 in (508 mm)                               |
| Dry Weight* Lightest model available          | 399 lbs / 181 kgs                                |
| Warranty**                                    | 1 year / 500 hours                               |
| CARB Star rating                              | 3  |