



Model: 225 HP

HP / kW	225 / 168
Full Throttle RPM	5800 - 6400
Bore x Stroke (in / mm)	3.23 x 3.23 in 82 x 82 mm
Cylinder Configuration	I-6
Displacement (CID/cc)	158.5 / 2598
Induction System	Supercharged with charge air cooling and electronic boost pressure control
Fuel Induction System	Sequential Multi-Port Electronic Fuel Injection (EFI)
Engine Control System	Smartcraft Digital Throttle & Shift (DTS)
Alternator Amp	70 amp / 882 watt (belt driven)
Starting	Smart Start Electric
Gear Case Ratio	4.8" (1.85 : 1) or 5.44" (1.85 : 1)
Steering	Electro-Hydraulic Power Steering
Counter Rotation	Available
Recommended Oil	Mercury Verado Oil 25 W 50
Recommended Fuel	92 Octane recommended; 87 Octane compatible (Up to 10% ethanol)
Engine Protection Operator Warning System	Smartcraft engine guardian
Compatible with Smarcraft Digital Technology	Yes
Shaft Length	L - 20 in (508 mm) XL - 25 in (635 mm) XXL - 30 in (762 mm)
Dry Weight* Lightest model available	635 lbs / 288 kgs
Warranty**	1 Year / 500 Hours
CARB Star Rating	2