

VERNATUBE™

Vernatube™ is resin-impregnated glass filament tubing wound exclusively with a new fire retardant resin formulated for high temperature applications. Centek uses the fire retardant Vernatube™ to fabricate many of the basic components used to manufacture our wet marine exhaust systems. Our Vernatube™ exceeds values for the class of materials designated as “self-extinguishing” per ASTM –D-635, UL94V-O, and the US Navy/USCG MIL-R-21607 and MIL-R-7575.

The smooth, resin-rich I.D. assures minimal flow restrictions to exhaust gases and cooling water flowing through the tubing. Our precise O.D. dimensions facilitate perfect connections between sections of the tubing and flexible joints or hoses.

PART#	NOMINAL O.D. IN/MM	NOMINAL WALL IN/MM	WEIGHT LBS. PER FT.	STD. LENGTH IN/MM
1100525	1.00 / 25	0.104	0.03	60.00 / 1524
1100521	1.50 / 38	0.105	0.40	120.00 / 3048
1100522	1.62 / 41	0.113	0.40	120.00 / 3048
1100523	1.75 / 44	0.112	0.40	120.00 / 3048
1100524	1.88 / 48	0.116	0.50	120.00 / 3048
1100512	2.00 / 51	0.125	0.50	120.00 / 3048
1100510	2.25 / 57	0.127	0.50	120.00 / 3048
1100511	2.38 / 60	0.127	0.60	120.00 / 3048
1100501	2.50 / 64	0.128	0.70	120.00 / 3048
1100513	2.88 / 73	0.130	0.80	120.00 / 3048
1100502	3.00 / 76	0.130	0.90	120.00 / 3048
1100503	3.50 / 89	0.135	1.00	120.00 / 3048
1100504	4.00 / 102	0.138	1.30	120.00 / 3048
1100505	4.50 / 114	0.140	1.50	120.00 / 3048
1100506	5.00 / 127	0.144	1.70	120.00 / 3048
1100507	6.00 / 152	0.148	2.00	120.00 / 3048
1100508	8.00 / 203	0.154	3.00	120.00 / 3048
1100509	10.00 / 254	0.160	3.80	120.00 / 3048
1100515	12.00 / 305	0.160	4.60	120.00 / 3048
1100514	14.00 / 356	0.200	6.50	144.00 / 3658
1100516	16.00 / 406	0.200	8.00	144.00 / 3658
1100529	18.00 / 457	0.200	8.50	144.00 / 3658